



**SpillFix
International**

SpillVac

SpillFix International introduces the revolutionary SpillVac

-  **Recover spills of all types**
-  **Minimise spillage - Transfer of products from container to container**
-  **Save time – Fast and powerful**
-  **Save money – recycle product thus reducing waste**
-  **Safe – air powered**
-  **Maintenance free – no internal moving parts**
-  **Versatile – accessories available to enable use in many areas**



From decanting liquids, cleaning up spills, cleaning plant and equipment to storing radiator coolant, the Spillvac has a place wherever there are liquids, semi liquids and solids.

Recovers spills of all types

Save time – Fast and powerful

Recycle product thus reducing waste

Applications

Decanting liquids - Transferring liquids - Spill clean up
Clean out of sumps, diffs, tanks, vats, deep fryers
Removal of viscous / semi viscous liquids
Sucks out injectors - Limitless applications

Industries using Spillvac

Agricultural Industry - Automobile Dealers and Service Shops
Boat & Marine Shops - City & County Shops - Department of Transportation
Detail Shops - Fabrication (CNC) Shops - Factories - Fluid Transport
Trailers - Heavy Equipment - Hydraulic Repair Shops
Junk Yards (Fluid Evacuation) - Lube Centres - Mining Industry
Powder Coating Shops - Power Plants - Refineries
Roadside Cleanup - School Districts (Bus Garages) - Tire Centres
Transit Companies - Transmission Shops - Truck companies

Spillvac accessories

Hose ware - Filters - Wands - Brushware
Absorbents - Pads - Environmentally friendly degreasers



49 litre:

Overall Height: 119cm Width / Length: 48cm x 46cm Weight empty: 22.5 kg
Suction: Draws 12 inches of mercury (3-4 times more powerful than most wet vacuums)
Material: Polished aluminium cylinder with galvanised fittings and brass valves
Power: Air powered. No electricity required.
Air compressor: 15 - 30CFM depending on application
Operating pressure: 90 psi
Suction hose: 3.18cm diameter 2.13 metres standard – static and corrosive free
Fill time: 28 seconds (water)
Discharge time: 20 seconds (water)

95 litre:

Overall Height: 112cm Width / Length: 69cm x 69cm Weight empty: 31.7 kg
Suction: Draws 12 inches of mercury (3-4 times more powerful than most wet vacuums)
Material: Polished aluminium cylinder with galvanised fittings and brass valves
Power: Air powered. No electricity required.
Air compressor: 15 - 30CFM depending on application
Operating pressure: 90 psi
Suction hose: 3.18cm diameter 2.13 metres standard – static and corrosive free
Fill time: 35 seconds (water)
Discharge time: 45 seconds (water)

170 litre:

Overall Height: 152cm Width / Length: 69cm x 69cm Weight empty: 38.5 kg
Suction: Draws 12 inches of mercury (3-4 times more powerful than most wet vacuums)
Material: Polished aluminium cylinder with galvanised fittings and brass valves
Power: Air powered. No electricity required.
Air compressor: 15 - 30CFM depending on application
Operating pressure: 90 psi
Suction hose: 3.18cm diameter 2.13 metres standard – static and corrosive free
Fill time: 1 min 45 seconds (water)
Discharge time: 50 seconds (water)

A 227 litre unit is also available. Enquire for details.



Distributor



www.SpillVac.com.au